



## HDMI MATRIX SWITCH 4K 4 X 4 MODEL : KVM0404K6

### FEATURES

- 1). 4 HDMI inputs, 4 HDMI standard / 2.0 outputs. Support HDR 10.
- 2). Manual or remote, IP Control - Web to select source input to different output.
- 3). Support Dolby TrueHD©, DTS-HD© Master Audio™
- 4). HDCP2.2 input , HDCP2.2 output . HDCP1.4 input, HDCP1.4 output
- 5). High-definition Resolutions support: HDTV - up to 1080p@60Hz, 4K@60Hz.
- 6). Panel Button, Local IR, RS232 Control command, IP Control, Web GUI Control
- 7). Multiple switching mode: push-in button, IR remote control, IR Routing, and RS-232 control



MATRIX SWITCH SERIES



### Package Contents

- 1). 1x HDMI Matrix
- 2). 1x 5V DC power supply
- 3). 1x Remote control
- 4). 1x IR Ext RX Cable
- 5). 1x Phoenix plugs for RS232 cable
- 6). 1x mounting kit
- 7). 1x CD software & user manual

# SPECIFICATIONS

<b>Operating Temperature</b>	-5° to 45°C
<b>Operating Humidity</b>	5 to 90%RH (No Condensation)
<b>HDCP Compliant</b>	HDCP2.2 and HDCP1.4
<b>Output Video</b>	HDMI2.0 and HDMI 1.4
<b>RS-232 serial port</b>	3 PIN, Terminal block
<b>IR Ext Port   USB Port</b>	1 x 3.5mm Stereo Jack   5p Micro USB Female.
<b>Ethernet Ports (IP control)</b>	RJ45, Female.
<b>Rack-mountable</b>	Standard Rack ears
<b>Data Transfer Speed Rate</b>	18Gbps
<b>Resolution</b>	1080p @ 60Hz, 4K@ 60Hz YUV 4:4:4
<b>Power Consumption</b>	13W (Max)
<b>Dimension (L x W x H)</b>	216 x 105 x 34
<b>Net Weight</b>	0.72 Kg

*Specifications are subject to change without notice. Mass and dimensions are approximate.*

# CONNECTION DIAGRAM

